

LANDSCAPE LIGHTS

Path Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-B301	3	12	0.717	4.18	2700K	190L	360	40"
TS-B302	3	12	0.708	4.23	2700K	158L	360	40"
TS-B306	3	12	0.729	4.11	2700K	96L	360	40"
TS-A6500C	2	12	0.693	2.88	2700-6500K	68L	120	70"

Accent Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-B102	4	12	0.732	5	2700K	382L	40	36"
TS-B105	5	12	0.758	7.45	2700K	383L	60	36"
TS-B106	8	12	0.771	9.132	2700K	435L	120	36"

Well Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-201	8	12	0.769	10.14	2700K	560L	120	32"
TS-203	4	12	0.731	4.812	2700K	308L	60	32"

HARDSCAPE LIGHTS

Paver Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-MHPL-6	1.5	12	0.75	2	4000K	32L	120	36"
TS-MHPL-8	1.8	12	0.75	2.4	4000K	52L	120	36"
TS-MPHL-9	2.5	12	0.75	3.35	4000K	62L	120	36"
TS-HPL-6	1.5	12	0.66	2	2700K	26L	120	36"
TS-HPL-8	1.8	12	0.678	2.556	2700K	44L	120	36"
TS-HPL-9	2.5	12	0.7	3.312	2700K	52L	120	36"

Pillar Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-PL100	3	12	0.717	3.816	2700K	195L	360	24"
TS-PL101	3	12	0.725	3.864	2700K	180L	360	24"
TS-PL102	6	12	0.778	7.332	2700-6500K	184L	360	24"

Hardscape Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-A3000C	0.8	12	0.63	1.26	2700-6500K	18L	120	70"
TS-A6000	1	12	0.65	1.45	2700K	85L	120	70"
TS-A6000C	2	12	0.63	2.85	2700-6500K	68L	120	70"
TS-MA6000	1	12	0.75	1.35	4000K	92L	120	70"

Dot Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-I5DOT-SS	0.25	12	0.607	0.27	4000K	12L	60	36"
TS-25DOT-SS	1.5	12	0.75	2	4000K	105L	60	36"
TS-M25DOTC-SS	1.2	12	0.75	1.6	2700-6500K	60L	60	36"
TS-I5DOT-BRZ	0.25	12	0.607	0.28	2700K	10L	60	36"
TS-25DOT-BRZ	1.2	12	0.75	1.6	2700K	90L	60	36"
TS-25DOTC-BRZ	1.5	12	0.75	2	2700-6500K	60L	60	36"

DECK LIGHTS

Post Cap Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-C125	2	12	0.686	2.78	2700K	18L	360	32"
TS-C125C	3	12	0.732	4.188	2700-6500K	22L	360	32"
TS-C130	2	12	0.679	2.65	2700K	30L	360	32"
TS-C140	3	12	0.732	5.11	2700K	32L	360	32"
TS-C140C	4	12	0.75	5.016	2700-6500K	32L	360	32"
TS-C145	3	12	0.711	4	2700K	27L	360	32"
TS-C145C	4	12	0.75	4.92	2700-6500K	30L	360	32"
TS-C150	3	12	0.711	4	2700K	40L	360	32"

Step Riser Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-A501	0.5	12	0.574	0.59	2700K	18L	180	70"
TS-A501C	1	12	0.639	1.404	2700-6500K	16L	180	70"
TS-A1001	1.5	12	0.669	2.39	2700K	123L	180	70"
TS-A1001C	2	12	0.681	2.544	2700-6500K	65L	180	70"

Surface Mounted Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-25WMA	2	12	0.685	2.93	2700K	44L	180	36"
TS-40WMA	1.5	12	0.684	1.99	2700-6500K	15L	180	36"

Tru-Post® Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TP-WL101A	3	12	0.75	4	2700K	126L	360	36"
TP-WL103A	3	12	0.75	4	2700K	184L	360	36"

STRUCTURE LIGHTS

Wall & Post Sconce Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TSS-AS200	3	12	0.713	3.805	2700-6500K	50L	360	36"
TSS-AS201	12	12	0.804	14.925	2700-6500K	802L	360	36"
TSS-AS202	6	12	0.754	6.816	2700-6500K	456L	360	36"
TSS-AS300	6	12	0.771	8.136	2700-6500K	300L	360	12"

Ceiling, Pendant & Bistro Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TSS-AC100	8	12	0.787	10.01	2700-6500K	392L	360	6"
TSS-API00	8	12	0.787	9.96	2700-6500K	392L	360	6"
TSS-AP400	2.5	12	0.689	3.4	2700-6500K	68L	360	42"
TSS-SL100	1	12	0.75	-	2700K	-	360	-

CONCRETE LIGHTS

Floor & Step Mounted Lights

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TSC-150	0.25	12	0.625	0.396	2700K	10L	60	36"
TSC-250C	1.5	12	0.671	2.316	2700-6500K	60L	60	36"
TSC-600C	1.5	12	1.56	2.304	2700-6500K	8L	45	36"

TRANSFORMERS

Indoor & Outdoor Transformers

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-TBPT-100	100	12	-	-	-	-	-	72"
TS-TSSA-200	200	12	-	-	-	-	-	42"
TS-TSSW-400	400	12	-	-	-	-	-	42"

REPLACEMENT LAMPS

Low Voltage Lamps

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-360G4-1	3	12	0.75	4	2700K	380	360	-
TS-360G4-C	1.5	12	0.75	2	2700-6500K	110	360	-
TS-120PAR36	8	12	0.75	10.65	2700K	850	120	-
TS-120PAR36-C	8	12	0.75	10.65	2700-6500K	640	120	-
TS-40MR16	4	12	0.75	5.35	2700K	400	40	-
TS-60-MR16-5.5W	5.5	12	0.8	8.85	2700K	480	60	-
TS-40MR16-C	8	12	0.75	10.65	2700-6500K	420	40	-

REPLACEMENT LIGHT MODULES

Low Voltage Replacement Modules

Model #	Wattage	Voltage	Power Factor (PF)	Voltage Amps (VA)	Kelvin	Lumens	Beam Angle	Wire Lead Length
TS-A3000-RLAMP-C	0.8	12	0.75	1.06	2700-6500K	18	120	-
TS-A6000-RLAMP	1	12	0.75	1.35	2700K	85	120	-
TS-A6000-RLAMP-C	2	12	0.75	2.60	2700-6500K	68	120	-
TS-MA6000-RLAMP	1	12	0.75	1.35	4000K	92	120	-